



DOMESTIC HOT WATER TANKS CLASS B & C WITH ONE HEAT EXCHANGER

EV 12S 300 65

SAP	301394
Capacity	283 L
Net weight	87 kg
Insulation	50 mm
Heat exchanger surface S1	1.45 m <sup>2</sup>
Heat exchanger capacity S1	8.8 L
Heat losses $\Delta T$ 45K	68 W
Energy class	B
Maximum operational temperature	95 °C
Maximum operational temperature of the heat exchanger	110 °C
Rated pressure of the water tank	8 bar
Rated pressure of the heat exchanger	6 bar



V40 - hot water delivered with a temperature of at least 40°C (S1)	435 L
Diameter	650 mm



- **HIGHLY EFFICIENT INSULATION** compliant with latest industry regulations – ERP Class B and C
- High quality **ENAMEL COATING CrystalTech PRO**
- **MAGNESIUM ANODES PROTECTION** of the inner tank surface for extended product life:
  - **TWO MG+** anodes for models from 160 L to 1000 L
- **SERVICE OPENING** for easy inspection and maintenance.
- Option for **INSTALLATION** of different power rated **HEATING ELEMENTS**.
- Thermoregulator installation pocket.
- Pockets for thermo sensors.

The range includes models from 160 L to 2000 L with energy efficiency class B or C. Suitable for installation in single and multi-family residential buildings as well as for commercial application.